

Revision Date: October 30, 2019
Issue Date: June 04, 2019
Project No. G103916546
Quote No.: Qu-00974263-0

Contact: Stella Su
Email: stella@nanhua.com
Phone No. 8602139126868-850

Report No. 103916546CRT-001

Shanghai Nanhua Electronics Co., Ltd.

Building #9
1755 Wenbei Road
Jiading
Shanghai 201802
China

Standards
<i>International Civil Aviation Organization (ICAO), Aerodromes, Annex 14, Volume 1, Eighth Edition, dated July 2018</i>

Test Purpose	ICAO Testing - Low Intensity Type C
Test Dates	May 1st, 2019 through May 31st, 2019

Revision October 30, 2019: Updated Model Number from LS730U to LS730U(L), added updated label photo



Jennifer Barnoski
Project Engineer
Lighting



Christopher W. Metcalf
Engineering Supervisor
Lighting

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Test Plan and Datasheets			
Client	Shanghai Nanhua Electronics Co., Ltd.	Engineer	Jennifer Barnoski
Report #	103916546CRT-001	Reviewer	Christopher W. Metcalf
Product	Low Intensity Obstacle Light	Model(s)	LS730U(L)
Standard	ICAO Annex 14, dated July 2018		

Spec	Test name	Clause	Pass Fail NA
ICAO	Photometry Low Intensity Obstacle Light - Type C	Table 6-1 & Table 6-2	Pass
ICAO	Chromaticity ICAO App. 1	1.2.3	Pass

Sample Information				
Date Rec.	Intertek ID	Description	Condition	Model No.
4/29/19	CRT1904291352-001	Low Intensity Obstruction Light	Production	LS730U(L)

Further Sample Description	
Type:	Low Intensity Type C Light
Options:	NA
Light Source:	[1] White LED, Elec-Tech International Co., Ltd, NLW3535AVR1
Lens:	Yellow PC (Sabic 2108T), Shanghai Nanhua Electronics Co., Ltd
Approx Size:	Diameter: 4", Height: 3"
Electrical Input:	12-24VDC
LED Supply Location:	Power supply integral to flashhead
Cable:	Length: 2.3m, Diameter: 4.5mm, Yuyao Yangli Electronics Co., Ltd
Casting Material:	ADC12
Mounting:	Magnetic Installation

Sample Information

Picture(s)



LS730U(L) P/N:
C型低光强障碍灯 B/N:
Low Intensity Aviation Obstruction Light
输入(Input):DC12-24V
平均功率(Average power):1.5W
防护等级(IP Rating):IP65

NANHUA Nanhua Electronics Co.,Ltd
+86 21 39128868
www.nanhua.com

上海南华机电有限公司 地址:上海市嘉定区福北公路1755弄9号

Photometry

Energize each light fixture and test for compliance with the photometric requirements. Operate the fixture until stabilized before taking measurements. Test distance was 100ft.

Results

Sample	Voltage Variation	Voltage	Position	Measured	Factor	Result
CRT1904291352-001	Input Voltage*	12.1	0,0	129	NA	NA
	Input Voltage +10%	26.4	0,0	129	100%	Pass
	Input Voltage -10%	10.8	0,0	129	100%	Pass

* Distribution test voltage

Parameter	Requirement	Measured	Result
Flash Rate (FPM)	60-90 FPM	79.2 FPM	Pass
Minimum Intensity (cd)	40cd between 2 and 10 degrees V	48.8 cd	Pass
Maximum Intensity (cd)	400cd at all radials	70.8 cd	Pass
Peak Intensity	Peak Located at approximately 2.5 degrees	6.5 degrees	Pass
Beam Spread	12 degrees (>20cd)	22.0 degrees	Pass

Cable Length:		NA	Calibration Factor:		2.45*10^-12		Input:		12.05	VDC		
Flash Duration (sec):		0.300	Neutral Density Filter:		NA							
Flash Period (sec.):		0.758										
Effective Intensity (cd)												
Vertical Position (deg.)	Horizontal Position (deg.)											
	0	30	60	90	120	150	180	210	240	270	300	330
19.0	X	X	X	X	X	X	X	X	19.2	19.2	X	X
18.5	19.6	X	X	X	X	X	X	X	20.0	21.2	X	19.2
18.0	21.2	X	X	X	X	X	X	X	21.2	22.4	X	20.4
17.5	22.4	X	19.2	X	X	X	X	X	23.6	23.2	X	22.4
17.0	23.6	19.6	20.4	X	18.4	X	X	19.2	24.0	24.4	X	24.0
16.5	25.6	22.0	22.4	X	20.0	18.4	19.6	20.0	24.8	26.0	X	25.2
16.0	26.8	23.2	24.0	X	22.4	20.0	21.2	22.0	26.8	27.2	19.6	26.0
15.5	28.8	26.0	26.0	19.6	24.4	22.4	22.8	24.0	28.0	28.8	20.8	26.8
15.0	30.4	26.8	27.6	24.8	25.6	24.0	24.8	25.6	29.2	30.0	22.4	28.8
14.5	32.8	28.8	29.2	22.8	27.6	25.6	26.4	26.4	30.4	31.6	24.8	30.4
14.0	35.2	30.4	30.8	24.8	29.2	27.6	29.2	28.4	32.0	34.0	26.8	32.0
13.5	37.2	32.4	32.8	27.6	31.2	28.8	31.6	30.8	33.6	35.2	28.8	33.6
13.0	39.2	34.4	34.4	30.0	32.8	32.0	34.4	33.2	34.8	37.6	30.8	34.8
12.5	41.6	36.4	36.8	33.2	35.6	33.6	36.4	34.8	36.8	39.6	34.0	37.6
12.0	43.6	39.2	39.6	37.2	38.4	36.8	39.6	38.0	38.4	41.6	36.0	38.8
11.5	46.8	42.4	43.2	41.6	42.8	40.0	44.0	40.8	41.6	45.2	38.0	40.8
11.0	49.6	46.0	46.0	46.0	46.0	43.6	47.2	43.6	45.6	40.8	42.8	44.0
10.5	54.0	49.6	49.6	49.2	49.6	48.4	51.6	48.8	49.6	44.4	45.6	47.6
10.0	57.2	53.2	53.6	53.6	52.4	51.6	54.8	52.0	53.2	48.8	50.0	51.6
9.5	60.4	56.8	56.0	56.8	56.0	55.2	58.4	55.6	56.8	52.4	53.2	54.0
9.0	63.2	60.0	60.4	60.4	59.2	58.8	61.6	58.4	58.4	56.4	56.8	56.4
8.5	65.2	62.8	62.0	63.2	62.4	62.4	64.8	62.0	61.2	60.0	59.6	59.2
8.0	65.2	64.4	64.0	66.0	63.2	65.2	67.6	65.6	60.8	60.8	61.2	60.8
7.5	64.8	65.6	65.2	66.4	63.2	67.2	68.8	67.6	61.2	62.4	62.8	61.6
7.0	64.0	66.4	66.0	66.8	64.4	69.2	68.8	67.6	61.2	62.0	63.6	62.8
6.5	62.8	67.2	66.8	66.8	63.2	70.8	68.4	68.8	60.8	62.4	64.4	62.4

6.0	62.4	67.2	67.2	67.2	63.2	70.4	68.8	69.2	60.8	62.8	64.4	62.4
5.5	61.6	66.8	68.0	67.2	62.4	69.6	68.0	69.6	60.8	62.0	62.4	62.4
5.0	61.2	66.0	66.4	67.6	61.6	68.8	67.2	69.2	62.0	62.8	61.6	62.0
4.5	61.2	65.2	68.0	66.8	61.6	68.4	66.4	69.2	62.4	62.0	62.0	61.2
4.0	61.2	64.8	66.8	66.4	62.0	67.2	65.6	69.2	61.6	62.8	60.8	60.0
3.5	60.8	63.6	66.4	65.6	61.2	66.0	64.4	68.0	61.6	62.0	60.0	59.2
3.0	60.0	64.0	65.2	64.8	60.8	65.6	63.2	67.2	60.8	60.8	58.8	58.8
2.5	58.8	63.2	64.8	64.4	61.2	64.0	62.8	66.8	60.8	58.8	58.8	56.0
2.0	58.4	62.8	64.0	64.0	60.8	62.8	61.2	64.8	60.0	58.0	57.2	55.2
1.5	58.4	62.4	64.4	63.2	60.0	62.0	59.6	64.4	59.6	57.6	57.2	54.4
1.0	58.0	61.6	64.0	63.2	60.0	61.2	59.2	63.2	58.8	56.4	56.8	53.6
0.5	57.6	60.8	64.0	62.0	59.6	61.2	58.4	62.4	58.0	55.6	55.2	52.0
0.0	56.8	58.8	62.8	61.2	59.6	61.2	58.8	61.6	58.4	53.6	54.0	51.2
-0.5	56.4	57.6	60.8	59.2	59.6	60.8	58.0	60.8	57.2	52.0	52.4	48.8
-1.0	56.0	55.2	59.2	58.8	57.6	59.6	57.6	59.2	55.2	50.4	50.4	48.4
-1.5	53.2	53.2	56.4	56.0	55.6	58.0	56.0	57.6	53.6	49.6	47.6	45.6
-2.0	50.4	51.2	53.6	54.0	53.6	56.0	54.4	55.6	50.8	47.2	44.4	43.6
-2.5	46.4	48.0	51.2	52.4	51.6	53.6	51.6	53.2	47.6	42.8	41.6	40.0
-3.0	44.4	44.4	47.6	50.0	47.6	51.6	49.6	50.0	44.0	39.6	39.2	36.0
-3.5	42.4	41.6	44.8	46.4	46.0	49.2	47.2	46.8	41.2	36.8	36.4	33.6
-4.0	39.6	39.2	42.0	42.8	42.8	47.2	44.0	44.0	38.0	33.2	33.6	30.8
-4.5	37.2	37.2	38.4	41.6	40.0	43.6	40.8	41.2	36.0	30.8	31.2	28.8
-5.0	35.2	34.4	36.4	39.2	37.2	40.8	38.4	38.4	34.0	29.2	28.0	26.4
-5.5	32.8	32.4	33.6	36.0	35.2	38.8	35.6	35.2	31.6	26.8	26.8	24.0
-6.0	30.4	28.8	30.4	34.4	32.4	35.6	32.4	32.4	28.8	24.4	24.0	22.0
-6.5	27.6	27.2	28.0	30.4	28.4	32.4	29.2	29.2	25.6	21.6	21.2	19.6
-7.0	25.6	24.8	25.2	29.2	26.4	29.6	27.2	26.8	23.2	19.2	19.2	X
-7.5	23.6	23.2	24.8	26.4	23.6	26.8	21.2	24.8	20.8	X	X	X
-8.0	22.0	22.4	22.4	24.4	22.4	25.2	23.2	22.0	18.0	X	X	X
-8.5	21.2	21.2	20.8	21.6	20.8	23.6	21.6	20.8	X	X	X	X
-9.0	20.0	19.2	19.2	21.2	19.2	22.0	18.4	19.2	X	X	X	X
-9.5	19.6	X	X	19.6	X	21.2	X	X	X	X	X	X
-10.0	X	X	X	X	X	19.6	X	X	X	X	X	X

ICAO Low-intensity Type C (Mobile Obstacle)

Min 2°-10°	57.2	53.2	53.6	53.6	52.4	51.6	54.8	52.0	53.2	48.8	50.0	51.6
Upper (°)	18	16.5	17	15	16	15.5	16	16	18	18.5	15.5	18
Lower (°)	-8.5	-8.5	-8.5	-9	-8.5	-9.5	-8.5	-8.5	-7.5	-6.5	-6.5	-6
Spread (°)	27	25	26	24	25	25	25	25	26	25	22	24
Max	65.2	67.2	68.0	67.6	64.4	70.8	68.8	69.6	62.4	62.8	64.4	62.8

Complies: YES NO

Tested By:	Brittany James	Signature or initials:	<i>Bj</i>
Engineer:	Lynette Smith	Signature or initials:	<i>Lynette Smith</i>
Reviewed By:	cwm	Signature or initials:	<i>cwm</i>
Test Equipment Used:	1, 2, 3, 4, 5, 6, 7	Sample No:	CRT1904291352-001
Amb (°C):	25.5	RH%	33.8
		Completion Date:	5/15/2019

Chromaticity ICAO

Wherever a color is referred to in this annex, the specifications for that color given in Appendix 1 shall apply.

Test the fixture with the lamp, filter and optical system for color of light emitted. Chromaticity Coordinates are to be calculated from a spectral distribution measured in 2nm increments for LEDs.

Results - ICAO LED Yellow

Sample	Color	Input	Location	x	y	z	(P/F)
CRT1904291352-001	Yellow	12.06	(0,6)	0.540	0.445	0.014	P

The aviation yellow must be per ICAO Annex 14, Volume 1, Appendix 1, Colors for Aeronautical Ground Lights, within the following chromaticity boundaries

Boundary	Line Equation	Calc.
Red Boundary	$y \geq 0.387$	0.445
White Boundary	$y \geq 0.980 - x$	0.440
Green Boundary	$y \leq 0.727x + 0.054$	0.447

Complies: YES NO

Tested By:	Brittany James	Signature or initials:	<i>BJ</i>
Engineer:	Lynette Smith	Signature or initials:	<i>Lynette Smith</i>
Reviewed By:	cwm	Signature or initials:	<i>cwm</i>
Test Equipment Used:	1, 2, 4, 5, 6, 7, 8	Sample No:	CRT1904291352-001
Amb (°C):	25.9	RH%	54.6
		Completion Date:	5/31/2019

Equipment list				
#	Intertek ID No.	Description	Manufacturer	Calibration Due
1	L178	100ft. Lab Goniophotometer	Labsphere	08-May-2020
2	E538	Oscilloscope	Tektronix	07-Sep-2019
3	L061	IL1700 Radiometer	International Light	14-May-2020
4	N1311	Precision Bubble Level	Starrett	10-Sep-2019
5	M308	Stopwatch	Traceable	03-Nov-2019
6	M135	Multimeter	Fluke	11-Jan-2020
7	M310	Hygro-Thermometer	Testo	16-Nov-2019
8	M292	OL750S Spectroradiometer	Gooch & Housego	30-Jun-2019
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				

Note: For measurement uncertainty, refer to the calibration certificates for all the test equipment located in the equipment files