

■ FC-02

■ Frangible Couplings (2-inch)



Compliance with Standards

SAC: GB/T 7256

ICAO: Doc 9157 Part 6 FAA: AC 150/5345-46


Application/Use

Applicable for installing elevated light on the flange

Features

- Forging of premium aluminum alloy material with thermal stability technology for even mechanical property
- Equal-strength structural design with even loading and less possibility of deforming
- High-precision machining, fully guarantees the quality and precision of bases
- Made of anti-corrosion aluminum with prior preservative treatment, durable in use

Structure



89 62 65

FC-02-I

I FC-02-O

Packing Data

FC-02-I

20 x frangible Couplings

net weight: 0.46 kg

FC-02-O

16 x frangible Couplings

net weight: 0.64 kg

Packing size: 340×340×190 mm³

Gross eight: 11.3 kg

Packing size: 340×340×190 mm³

Gross eight: 12.3 kg

Ordering Information

Type

FC-02-X-X

FC-02-X

FC-02-X-X

FC-02-X

FC-0

 $G=55^{\circ}$ cylindrical pipe thread $NPT=60^{\circ}$ american national taper pipe thread $NPS=60^{\circ}$ american national straight pipe thread

Installation



Fig 1. On FL-10 Flange



Fig 2. On FL-12 Flange

* All rights reserved, subject to modifications